

Ingersoll Rand Wadco

MANUAL CHAIN PULLEY BLOCK

MANUAL CHAIN PULLEY BLOCK



SMA Series Manual Chain Hoist Features

A NEW design for today's job site, with safety and performance in mind. Meets or exceeds world specifications including ASME B30.16. A value line product with premium features at a great price.

- Unique Overload Protection to deter and reduce downtime and repair costs resulting from abuse.
- All steel, low headroom, light weight construction.
- Self-adjusting disc type double pawl mechanical load brake.
- Hardened roller bearings for maximum efficiency and durability.
- Improved 4 layer finish of nickel, copper, nickel and chrome
- Complementing our Silver Series lever hoist companion product.
- Ideally suited for the Rental and Construction markets.
- Standard lift (L) is 10 feet, Hand chain drop (D) is 2 feet less than lift (unless specified).

SPECIFICATIONS

Model No.	Capacity		Pull to lift rated load lbs	Chain o 'hauled to lift load 1 ft	Net wt of chain per ft of lift lbs	No. of Chain falls	Load chain size mm	Ship wt w/10 ft of lift lbs
	Metric tons	lbs						
SMA005	½	1100	48	25	.55	1	6.3 x 18	18
SMA010	1	2200	75	39	.55	1	6.3 x 18	26
SMA015	1½	3300	84	58	.80	1	8.0 x 24	39
SMA020	2	4400	81	75	1.10	2	6.3 x 19	35
SMA030	3	6600	90	116	1.60	2	8.0 x 24	55
SMA050	5	11000	97	187	1.40	2	10.0 x 30	86

Note:
Standard lift 10 feet

LEVER CHAIN HOIST

LEVER CHAIN HOIST



SL Series Lever Chain Hoist Features

Our value priced lever hoist with industrial rated performance. One hand operation with the best free chaining available. If a load is applied in the free chain mode, the brake will automatically engage, minimizing operator setup error.

- 1/2 - 6 ton capacities.
- All steel construction.
- 360 degree handle rotation.
- Rubber handle grip in all sizes.
- Reliable disc brake.
- Premium grade 100 alloy load chain.
- Hardened swivel-latch hooks.
- Light weight.
- Low handle force.
- Short handle stroke.
- Standard lifts of 5, 10, 15, and 20 feet. Longer lifts available.

SPECIFICATIONS

Model No.	Capacity		Pull to lift rated load lbs	New wt of Chain per ft of lift lbs	No. of Chain falls	Load chain size mm	Ship wt w/10 ft of lift lbs
	Metric tons	lbs					
SL100	1/2	1100	77	0.36	1	5.0 x 15.0	11.2
SL150	3/4	1650	68	0.53	1	6.0 x 18.0	15.5
SL200	1	2200	64	0.53	1	6.0 x 18.0	15.4
SL300	1-1/2	3300	73	11.73	1	7.1 x 21.2	24.3
SL600	3	6600	75	1.48	1	10.0 x 30.0	44.1
SL1200	6	13200	81	2.95	1	10.0 x 30.0	67.1

Standard lift 5, 10, 15, and 20 ft

Models shown above are a representative selection of our extensive range. Please contact IR Wadco for details on additional models.